Detailed Specifications

Model # 1454

Name Servus Firefighter

Country of Origin USA

Description 16" Firefighter Non-Insulated Bunker

Height 16"



| Size Range | Whole & Half sizes 5 - 16 |
|----------------------------|--|
| Width | Narrow A/B/C |
| | Medium D/E |
| | Wide EE/EEE |
| Type of Construction | Vulcanized Layered Rubber |
| 3rd Party Certification | U.L. Classified, 72S4 |
| | The Quality System for Norcross Safety Products is Certified to ISO 9001 |
| Compliance | NFPA - National Fire Protection Assoc. 1971 Standard on Protective Ensemble for Structural Fire Fighting 2000 Edition |
| | ANSI - American National Standard Z41-1999 |
| | OSHA - Occupational Safety/Health Admin. 1988 Code of Federal Registry 1910.36,1910.156 and Appendix E |
| | CAL-OSHA - Calif. Admin code Title 8 GISO Article 10.1 Sept 1985 |
| | CSA - Canadian Standards Assoc. Master Contract #205043 |
| Upper | Rubber Formulation is fire resistant, resists cracking and oxidation |
| Lining | 20 oz Grey Felt |
| Outsole | White High Abrasion |
| Outsole Pattern | White Heavy Trac Tread Design |
| Heel | Black Molded Rubber |
| Heel Reinforcement | Cotton / Nylon blend |
| Insole | 3/8" Cushion Sponge |
| Steel Toe | Meets ANSI Z41 1999- Section 1 Impact & Compression |
| Steel Midsole | One Piece Stainless |
| Steel Shank | .05" x 1" x 4" Triple Ribbed |
| Bar Coding | Each pair of Servus boots has a unique barcoded serial number in the right boot to assist in asset tracking. This unique number is also printed in numeric form. |