

AlphaTec®

66-320

PVC, Greenish yellow, 430 g/m²

Formerly known as TRELLECHEM® SPLASH 900

Full-body splash protection designed for use by both emergency back-up teams and in industry.

- Rear-entry full-body splash protection
- Available with double open legs or sewn-in socks
- Made from a strong, soft and flexible fabric, ensuring wearer comfort
- Suit material is antistatic
- Provides good protection against alkalis and acids
- Offers protection against infective agents
- Certified to EN 14605:2005, type 3 (liquid-tight)

Applications

- Chemical Handling
- Emergency Teams
- Fire & Rescue Service
- First Response
- Hazmat Teams
- Industrial and Tank Cleaning
- Petrochemicals



Anatomically designed face seal for optimum safety and comfort.



Rear-entry watertight PVC zipper, placed horizontally across the shoulders. Covered by a zip flap with hook-and-loop closure.



Bayonet glove ring system for quick and simple glove exchange.



Double open legs (model 151)
alternatively sewn-in socks (model 156)



Splash Protection



Re-usable



Material Construction

POLYAMIDE FABRIC

PVC

AlphaTec®

66-320

PVC, Greenish yellow, 430 g/m²

PRODUCT INFORMATION

AlphaTec® 66-300, PVC 390 g/m ² - Model Description			
	Material	Model	Design features
AlphaTec®	66-320	151-G09	Open double legs, Bayonet rings + AlphaTec® (Scorpio) #08-354 gloves
		156-G09	Sewn-in socks, Bayonet rings + AlphaTec® (Scorpio) #08-354 gloves

AlphaTec® 66-320, PVC 430 g/m ²	
Design	Rear-entry non-encapsulating suit, hood with face seal
Garment material	Strong and flexible polyamide fabric, single coated with PVC. Material weight: 430 g/m ² . PVC is suitable for protection against alkaline chemicals in all concentrations, such as sodium hydroxide and ammonia, and against low to medium concentration acids, such as hydrochloric acid.
Seams	Double welded.
Face Seal	Anatomically designed rubber face seal.
Gloves & Attachments	AlphaTec® (Scorpio) #08-354 gloves. The gloves are attached with a Bayonet glove ring system, which offers quick and simple glove exchange.
Legs/Footwear	Double open legs, i.e. inner leg with foot strap & outer splash guard (Model 151). Alternatively sewn-in socks (Model 156). Boots are not included but available to order.
Reinforcements	Knees and elbows are reinforced to provide extra abrasion resistance.
Zipper	Rear-entry watertight PVC zipper. The zipper is placed horizontally across the shoulders for ease of donning, and is protected by a splash guard/flap with hook-and-loop closure.
Colour	Greenish yellow.
Sizes	XXS - XXXL
Included with each delivery	<ul style="list-style-type: none">• 2 pcs extra locking pins for the Bayonet glove ring system• 1 pce Molycote lubrication for the O-rings in the Bayonet glove ring system• 1 pce grease stick for lubrication of the zipper
Standards & Approvals	<ul style="list-style-type: none">• EN 14605:2005 + A1:2009, type 3 (liquid-tight)• EN 14126:2003 (infective agent protection)• EN 1149-5:2008 (antistatic suit material)

For additional information, visit us at protective.ansell.com or contact us at:

Ansell Protective Solutions AB
Arenagatan 8B
215 33 Malmö
Sweden
Tel. + 46 10 205 1800
order.protective@ansell.com

Europe, Middle East and Africa
Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
Tel. + 32 2 528 74 00
Fax + 32 2 528 74 01
info.europe@ansell.com

Latin America & Caribbean
Ansell Brazil Ltda.
Rua das Figueiras 474 – 4º Andar
Bairro Jardim
SP 09080-300 Santo André, Brazil
CNPJ: 03.496.778/0001-21
+55 11 3356 3100
sac@ansell.com

North America
Ansell Healthcare LLC
111 Wood Avenue South, Suite 210
Iselin, NJ 08830, USA
Tel. + 1 800 800 0444
Fax. + 1 800 800 0445
info@ansell.com

Asia Pacific
Ansell Protective Solutions Singapore Pte. Ltd.
237, Pandan Loop,
#05-05 Westech Building
128424 Singapore
Tel. + 65 6908 4115
order.protective@ansell.com

Performance Standards



TYPE 4



EN 14126



EN 1149-5

EN 1149-5:
This applies only to the suit material.