

Guardman brunaslöngur

Innra þvermál		Þyngd pr. m.	Sprengi- þrýstingur	Þvermál 25 m. slöngu m/tengju	Lengdir fánlegar í öllum stærðum
Tommur	mm				
1	25,4 + 1,6	275 g	7,0 Mpa	45 sm	15, 20, 25 eða 30 m Hægt að fá lengdir upp í allt að 200 m. Hitaból frá 70°C til -30°C. Hitaból í stuttan tíma 100°C
1 ½	38,0 + 1,6	300 g	5,5 Mpa	45 sm	
-	42 mm + 1,6	310 g	5,0 MPa	45 sm	
1 ¾	45,0 + 1,6	360 g	4,5 MPa	45 sm	
2	51,0 + 2,0	380 g	4,5 MPa	45 sm	
2 ½	65,0+2,0	530 g	4,5 MPa	45 sm	
3	76,0 + 2,0	700 g	4,0 MPa	45 sm	
3 ½	90,0 + 2,0	1000 g	4,0 MPa	45 sm	
4	102,0 + 2,5	1050 g	3,5 MPa	48 sm	
6	150,0 + 3,0	1700 g	3,6 Mpa	50 sm	

1 Mpa = 10 Bar Vinnuþrýstingur = 1/3 af sprengiþrýstingi.