



Master Stream Nozzle

WWW.PROTEKFIREFIRE.COM



Style #823

- Lightweight Alloy Construction
- Combination of narrow fog, wide fog and straight stream
- Flow remains constant in all patterns
- Vary flow settings (300, 500, 700 GPM) with easy turn of the spring-loaded baffle
- "Built-in" stream shaper for maximum reach
- Fully machines waterway for superior stream quality
- Precision machined teeth for full fog pattern
- Grease fitting for easy maintenance
- Excellent for Protek Portable Monitor



Spring-loaded baffle for easy change of flows



"Built-In" Stream Shaper for maximum reach

Style	Inlet	Flow Rate	Length	weight
823-BC	2-1/2"	300, 500, 700 GPM (1,140, 1,900, 2,660 LPM)	7"	4lb



Protek
Firefighting Equipment

Master Stream Nozzle



WWW.PROTEKFIREFIRE.COM

823, 823-BC Master Stream Nozzle										
Style	Nozzle Pressure		Flow Setting		Actual Flow		Straight Stream Reach			
	PSI	BAR	GPM	LPM	GPM	LPM	Effective		Overall	
							Feet	Meters	Feet	Meters
823 & 823-BC	75	5	300	1140	260	985	150	45	160	48
			500	1900	435	1645	175	53	185	56
			700	2660	605	2290	180	55	190	58
	100	100	300	1140	300	1140	170	51	180	54
			500	1900	500	1900	200	60	210	64
			700	2660	700	2660	205	62	215	65
	125	125	300	1140	335	1265	190	58	200	60
			500	1900	560	2120	220	67	230	70
			700	2660	785	2970	220	67	230	70

