

Selectable Gallonage Nozzles

Style 360, 361, 362



- Combination pattern nozzles with versatile multiple flow settings
- Produces straight stream for maximum reach and superb wide fog pattern for optimum fire fighter protection
- Available in either lightweight hardcoat anodized aluminium or corrosion resistant brass construction
- Available in tip only and shutoff combinations
- Standard operating pressure at 100 psi (7 bar), optional 85 psi (6 bar) or 75 psi (5 bar)
- Style 360 and 362 can be used for high pressure applications up to 580 psi (40 bar) hydrostatic pressure
- Minimal maintenance reflected in robust design, precision machining and quality materials
- Standard NH inlet or optional BIM / Machino / Storz inlets
- Optional 1-1/2" inlet size
- Compatible with Foam Tube Style 210
- Conforms to all aspects of NFPA 1964 (Spray Nozzles, Shutoff and Tips)

Specification

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
360	1"(25mm)	7.4"(190mm)	2.3(1.1kg)	5-10-24-40	19-37-90-150
361	1"(25mm)	7.4"(190mm)	2.3(1.1kg)	13-25-40-60	50-100-150-230
362	1"(25mm)	7.4"(190mm)	2.3(1.1kg)	12-23-30	50-90-115



Selectable Gallonage Nozzles

Unique Features On Protek Nozzles

Style 360

- Laser-etched anodized label for excellent durability and visibility
- Unique series number etched for easy identification
- New and improved handle design
- Reinforced metal pieces improve durability
- Stainless filter mesh prevents blockage caused by debris
- Choice of 1" or 1-1/2" swivel inlet
- Heavy-duty chrome plated metal shutoff ball for smooth action and long life
- Ergonomic design pistol grip (available in various colours)
- Flow pattern detents facilitate positive positioning and smooth action
- Large metal flow selection ring for enhanced grip
- Raised lug for easier pattern identification
- Flush without changing pattern or shutting down
- Baffle etched with pressure (psi and bar)

Stainless steel spinning teeth

Heavy-duty chrome plated metal shutoff ball for smooth action and long life